

TECHNICAL SPECIFICATION



2m Webbing Anchorage Sling

2m Webbing Anchorage Sling / FAR0504



DESCRIPTION

2m Webbing Anchorage Sling made from 20mm wide polyester webbing. 25kN breaking strength.

OPTIONS

2m Webbing Anchorage Sling (FAR0504)

SAFETY STANDARDS

EN 795



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsspsafety.com / Web: www.jsspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 6 Jan 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Length
2m

Material
20mm Wide Polyester Webbing



Rated Weight / Load
20kN Breaking Strength



Product Weight
250g

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Trains

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0504-far0514.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 6 Jan 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

