TECHNICAL SPECIFICATION



2m Self-Retractable Lifeline with Scaffold Hook

2m Self-Retractable Lifeline with Scaffold Hook / FAR0731



DESCRIPTION

2m lightweight self-retractable lifeline, in robust and durable plastic casing. Webbing width 21mm with shock absorber. Equipped with 1 quarter turn gate aluminium connector and 1 aluminium scaffold hook.

Horizontal use (Sharp Edge VG 11 RFU CNB/P/11.060), fall factor 2 use in the limit of 100kg.

OPTIONS

2m Self-Retractable Lifeline with Scaffold Hook (FAR0731)

SAFETY STANDARDS

EN 360





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







SPECIFICATIONS

Fall Indicator

No

Material

21mm Wide Webbing

Sharp Edge

Yes



Rated Weight / Load

140kg (100kg For Horizontal and Fall Factor 2 Use)

Delivered With

1 Quarter Turn Aluminium Connector. Gate Opening 21mm. Conforms to EN362 Class B. 1 Aluminium Scaffold Hook. Gate Opening 60mm. Conforms to EN362 Class A/T Length 2m

Shock Absorber

External

Casing

Robust and Durable Plastic



Product Weight

1244g

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Aeronautics Steel Frame

Wind Turbines

DOWNLOADS

Image Pack (ZIP)

doc-far0701-far0731.pdf (PDF)









