

## TG6240

Conforming to cut level E under the new EN388:2016 standard, TG6240 has unrivalled levels of dexterity and comfort and is designed to last for long periods of time.


The MicroDex Ultra coating and new Life Extending Technology makes the TG6240 perfect for high cut risk tasks in wet, dry and oily conditions. Also features a thumb crotch to further extend the wear life of the glove.

The LXT range is certified as carbon neutral from cradle to grave. This means that at no extra cost, your LXT glove has helped to lessen its impact on the environment.

### Ideal for

- Automotive
- Construction and utility
- Engineering and manufacturing
- Oil and gas
- Rail
- Mechanical and electrical
- Waste, recycling and local authority



<b>EN 388</b>	4X44E
<b>Sizes</b>	5-12
<b>Liner</b>	Polyester/Glass HPPE/Steel/ Nylon/Elastane
<b>Gauge</b>	15gg
<b>Coating</b>	MicroDex Ultra
<b>Conditions</b>	

EN 388:2016



4 X 4 4 E



EN 407:2020



X 1 X X X X

**Qty/band** 10 pairs

**Qty/carton** 100 pairs



**KEY**

-  Dry
-  Wet
-  Heat
-  Oily
-  Cold
-  Chemical



Carbon neutral



Plastic free packaging



Conforms to EN 407:2020



Resistance to oil & water



Reduction in cost in usage



Comfort & durability



Washable to 40°C  
Certified up to 3 washes



Reduction in waste & landfill

0.7391 KgCO<sub>2</sub>e /pair  
(Prior to carbon inset)